



The DB range of purpose designed quality acetal fittings provide high retention in low pressure poly tubing for long-term reliability of connections.

### Features

- Double barb for increased retention.
- Sharp-edged barbs create leak-proof seal.
- Increased strength and superior quality.
- Heat chemical and wear resistant.
- UV stabilized materials for long life.

### Applications

Low pressure micro irrigation systems.



DB Coupling

### DB Coupling

TYPE	PART NUMBER	PACK QUANTITY	PACKS PER CARTON	CARTON (lbs)
DB COUPLING 13 mm (tube ID .520)	47005	25	50	13.8
DB COUPLING 14 mm (tube ID .530)	47015	25	40	12.8
DB COUPLING 15 mm (tube ID .570)	46975	25	50	18.0
DB COUPLING 16 mm (tube ID .600)	47025	25	50	18.8
DB COUPLING 18 mm (tube ID .660)	47035	25	40	17.7
DB COUPLING 21 mm (tube ID .805)	47045	25	30	16.8
DB COUPLING 25 mm (tube ID 1.050)	46995	25	20	15.8



DB Reducing Coupling

### DB Reducing Coupling

TYPE	PART NUMBER	PACK QUANTITY	PACKS PER CARTON	CARTON (lbs)
DB REDUCING COUPLING 16 mm x 14 mm	47075	25	50	18.1
DB REDUCING COUPLING 18 mm x 14 mm	47085	25	50	20.1
DB REDUCING COUPLING 25 mm x 13 mm	47065	25	32	19.1
DB REDUCING COUPLING 25 mm x 14 mm	47105	25	32	20.7
DB REDUCING COUPLING 25 mm x 15 mm	47135	25	28	17.5
DB REDUCING COUPLING 25 mm x 16 mm	47145	25	28	17.8
DB REDUCING COUPLING 25 mm x 18 mm	47175	25	26	17.2
DB REDUCING COUPLING 25 mm x 21 mm	46965	25	24	17.0



DB Elbow

### DB Elbows

TYPE	PART NUMBER	PACK QUANTITY	PACKS PER CARTON	CARTON (lbs)
DB ELBOW 13 mm (tube ID .520)	47205	25	50	16.1
DB ELBOW 14 mm (tube ID .530)	47215	25	50	19.6
DB ELBOW 15 mm (tube ID .570)	47375	25	50	21.7
DB ELBOW 16 mm (tube ID .600)	47225	25	40	18.5
DB ELBOW 18 mm (tube ID .660)	47235	25	40	21.5
DB ELBOW 21 mm (tube ID .805)	47245	25	20	14.6
DB ELBOW 25 mm (tube ID 1.050)	47255	25	16	16.3



DB Reducing Elbow

### DB Reducing Elbows

TYPE	PART NUMBER	PACK QUANTITY	PACKS PER CARTON	CARTON (lbs)
DB REDUCING ELBOW 16 mm x 14 mm	47275	25	50	21.1

\* Sizing chart available at [www.antelco.com](http://www.antelco.com)

# DB Fittings



The DB range can be confidently installed without clamps when matched to quality low pressure poly tubing with corresponding dimensions (refer to the tubing manufacturer for confirmation of suitability or test under field conditions).

Operating pressures should not exceed 50 psi.



DB Tee



DB Increasing Tee



DB Reducing Tee



DB Male Adapter



DB End Plug

## DB Tees

TYPE	PART NUMBER	PACK QUANTITY	PACKS PER CARTON	CARTON (lbs)
DB TEE 13 mm (tube ID .520)	47405	25	40	18.6
DB TEE 14 mm (tube ID .530)	47415	25	30	17.3
DB TEE 15 mm (tube ID .570)	47395	25	30	18.6
DB TEE 16 mm (tube ID .600)	47425	25	25	16.8
DB TEE 18 mm (tube ID .660)	47435	25	20	16.0
DB TEE 21 mm (tube ID .805)	47445	25	12	12.5
DB TEE 25 mm (tube ID 1.050)	47455	25	10	14.8

## DB Increasing Tees

TYPE	PART NUMBER	PACK QUANTITY	PACKS PER CARTON	CARTON (lbs)
DB INCREASING TEE 14 mm line x 16 mm branch	47475	25	30	18.3

## DB Reducing Tees

TYPE	PART NUMBER	PACK QUANTITY	PACKS PER CARTON	CARTON (lbs)
DB REDUCING TEE 13 mm line x 4 mm branch	47765	25	50	19.6
DB REDUCING TEE 14 mm line x 4 mm branch	47465	25	50	21.3
DB REDUCING TEE 25 mm line x 13 mm branch	47585	25	10	12.5
DB REDUCING TEE 25 mm line x 14 mm branch	47695	25	10	12.7

## DB Male Adapter

TYPE	PART NUMBER	PACK QUANTITY	PACKS PER CARTON	CARTON (lbs)
DB MALE ADAPTER 13 mm x 1/2" MNPT	48035	25	50	22.8
DB MALE ADAPTER 14 mm x 1/2" MNPT	48015	25	50	22.6
DB MALE ADAPTER 15 mm x 1/2" MNPT	48025	25	50	22.9
DB MALE ADAPTER 16 mm x 1/2" MNPT	48045	25	40	18.5

## DB End Plugs

TYPE	PART NUMBER	PACK QUANTITY	PACKS PER CARTON	CARTON (lbs)
DB END PLUG 13 mm	47685	25	50	12.0
DB END PLUG 14 mm	47615	25	50	13.3
DB END PLUG 16 mm	47625	25	50	15.9
DB END PLUG 18 mm	47635	25	50	18.5
DB END PLUG 21 mm	47645	25	40	18.4